

LCG-CL

35W, 40W, 60W, 90W

THE **L** **E** **D** ADVANTAGE

Canopy

LED Canopy Lighting



LED CANOPY LIGHT

📌 **LCG-CL** 35W, 40W, 60W, 90W

Project Name

Notes

MODELS



FEATURES

- Universal voltage 110-277V or high voltage 200-480V
- Dimmable / Non-dimmable
- Excellent optical design
- Die-cast aluminum design, better cooling

APPLICATIONS

Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent. Applications include manufacturing, warehousing and other large indoor spaces.

WARRANTY

Five-Year Warranty

SPECIFICATIONS

Ordering Information: Example: [LCG-CL] - [60W] - [40K] - [U] - [BK]

Model #	Input Power	CCT	Rated Lumens	Voltage	Finish	Option
LCG-CL	[35W] 35W [40W] 40W [60W] 60W [90W] 90W	[30K] 3000K [40K] 4000K [50K] 5000K [65K] 6500K	3000 lm 4000 lm 5100 lm 7800 lm	[U] 100-277V [H] 200-480V AC	[BK] Black [WT] White	[-] Non Dimming [D] Dimmable [SP] Sensor [-] No Sensor

LISTINGS / CERTIFICATES

C-UL US certified to US and Canadian safety standards. Damp location listed. For use in ambient operating temperatures ranging from -40°C to 40°C.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified. nlights.org/QPL to confirm which versions are qualified.



PHOTOMETRIC DISTRIBUTION

